

Chapter 22

Configuring Local and Global Parameters with the C-Web Interface

This chapter describes how to configure global and local parameters with the C-Web Interface. You can also use the following to configure parameters:

- To use the SRC CLI, see *SRC-PE Services and Policies Guide, Chapter 10, Configuring and Managing Policies with the SRC CLI*.
- To use Policy Editor, see *SRC-PE Services and Policies Guide, Chapter 9, Configuring Local and Global Parameters with Policy Editor*.

Topics in this chapter include:

- Viewing Predefined Global Parameters with the C-Web Interface on page 231
- Configuring Global Parameters with the C-Web Interface on page 232
- Configuring Local Parameters with the C-Web Interface on page 232
- Viewing Runtime Parameters with the C-Web Interface on page 233

Viewing Predefined Global Parameters with the C-Web Interface

To view predefined global parameters:

1. Click **Configure > Policies**, and then expand Global Parameters.

Configuring Global Parameters with the C-Web Interface

If you change global variables for policies, the change takes effect the next time a service is activated; the change does not take effect for active service sessions.

To create a global parameter:

1. Click **Configure > Policies**, and select **Global Parameters**.
2. In the Create new list, select **Parameter**. Type a name for the new parameter, and click **OK**.
3. Enter information as described in the help text in the main pane, and click **Apply**.

Related Topics

For valid values of each parameter type, see *SRC-PE Services and Policies Guide, Chapter 8, Overview of Using Local and Global Parameters*.

Configuring Local Parameters with the C-Web Interface

You create local parameters within a policy group.

To configure local parameters:

1. In the side pane, expand a policy group, and select **Local Parameters**.
2. In the Create new list, select **Parameter**. Type a name for the new parameter, and click **OK**.
3. Enter information as described in the help text in the main pane, and click **Apply**.

Related Topics

For valid values of each parameter type, see *SRC-PE Services and Policies Guide, Chapter 8, Overview of Using Local and Global Parameters*.

Viewing Runtime Parameters with the C-Web Interface

Runtime parameters are parameters that are filled in with an actual value from the running system when the policy is installed. The SRC software comes with many predefined runtime parameters.

To view runtime parameters:

1. Click **Configure > Policies > Global Parameters > Runtime Parameters**.
2. In the side pane, select the runtime parameter that you want to view.

