

## Chapter 11

# Managing SRC Components with the CLI

This chapter describes how you can start, stop, and view status of SRC components from the CLI. Topics include:

- Verifying Status of SRC Components on page 103
- Enabling SRC Components on page 104
- Disabling an SRC Component on page 104
- Restarting an SRC Component on page 105

## Verifying Status of SRC Components

---

To view information about the status for SRC components:

```
user@host> show component
Installed Components
Name      Version                                     Status
cli       Release: 7.0 Build: CLI.A.7.0.0.0171     running
acp       Release: 7.0 Build: ACP.A.7.0.0.0174     disabled
jdb       Release: 7.0 Build: DIRXA.A.7.0.0.0176   running
editor    Release: 7.0 Build: EDITOR.A.7.0.0.0176  disabled
redir     Release: 7.0 Build: REDIR.A.7.0.0.0176   disabled
licSvr    Release: 7.0 Build: LICSVR.A.7.0.0.0179  stopped
nic       Release: 7.0 Build: GATEWAY.A.7.0.0.0170 disabled
sae       Release: 7.0 Build: SAE.A.7.0.0.0166     running
www       Release: 7.0 Build: UMC.A.7.0.0.0169     disabled
jps       Release: 7.0 Build: JPS.A.7.0.0.0172     disabled
agent     Release: 7.0 Build: SYSMAN.A.7.0.0.0174  disabled
webadm    Release: 7.0 Build: WEBADM.A.7.0.0.0173  disabled
```

## Enabling SRC Components

---

On a C-series Controller, you can enable all SRC components from the CLI. On a Solaris platform, you can enable the subset of components supported by the CLI.

You can enable the following SRC components from the CLI:

- Admission Control Plug-In (ACP)
- Service activation engine (SAE)
- C-Web
- Juniper Networks database
- Juniper Policy Server (JPS)
- Network Information Collector (NIC)
- Policy and Services Editor
- Redirect Server
- SNMP agent

To enable a component:

- In operational mode, use the `enable component` command. For example:

```
user@host> enable sae
```

## Disabling an SRC Component

---

On a C-series Controller, you can disable a running SRC component from the CLI. On a Solaris platform, you can disable a running component that is supported by the CLI.

To disable a component:

1. Verify which components are running by entering the `show component` command in operation mode:

```
user@host> show component
Installed Components
Name          Version                                     Status
cli           Release: 7.0 Build: CLI.A.7.0.0.0171     running
acp           Release: 7.0 Build: ACP.A.7.0.0.0174     disabled
jdb           Release: 7.0 Build: DIRXA.A.7.0.0.0176   running
editor        Release: 7.0 Build: EDITOR.A.7.0.0.0176  disabled
redir         Release: 7.0 Build: REDIR.A.7.0.0.0176   disabled
licSvr        Release: 7.0 Build: LICSVR.A.7.0.0.0179   stopped
nic           Release: 7.0 Build: GATEWAY.A.7.0.0.0170  disabled
sae           Release: 7.0 Build: SAE.A.7.0.0.0166     running
www           Release: 7.0 Build: UMC.A.7.0.0.0169     disabled
jps           Release: 7.0 Build: JPS.A.7.0.0.0172     disabled
```

```
agent      Release: 7.0 Build: SYSMAN.A.7.0.0.0174      disabled
webadm     Release: 7.0 Build: WEBADM.A.7.0.0.0173     disabled
```

2. Disable a component by using the `disable component` command in operational mode. For example:

```
user@host> disable sae
```

## Restarting an SRC Component

---

If an SRC component is enabled, you can restart it if needed. You can use one of the following methods to restart a component:

- `gracefully`— Shuts down the component, then starts it again. (Default)
- `immediately`— Sends a signal kill (SIGKILL) signal to immediately stop the component, then starts it again.
- `soft`—Sends a signal hangup (SIGHUP) signal to the process for the component, then starts it again.

To restart an SRC component:

- In operational mode, use the `restart component` command.

```
user@host restart component component <gracefully | immediately | soft>
```

For example, to restart the SAE gracefully:

```
user@host restart component sae gracefully
```

